

Gun Range

HEALTH & SAFETY | PREVENTION | GOOD HOUSEKEEPING



TIGER-VAC.COM

Tiger-Vac®
...The name to vacuum with

SPECIALIZING IN THE DESIGN AND MANUFACTURE
OF LEGALLY CERTIFIED PORTABLE INDUSTRIAL VACUUM
AND DUST COLLECTION SYSTEMS FOR CONTAMINATION
CONTROLLED ENVIRONMENTS AND HAZARDOUS LOCATIONS
Since 1983

VACUUMING IS THE SAFEST METHOD FOR RECOVERING HAZARDOUS AND COMBUSTIBLE DUST

How you clean the range area is very important. Inadequate and/or inappropriate range cleaning procedures can actually create a greater risk of lead exposure. Perhaps the worst thing you can do is clean the range by dry sweeping. This procedure will stir up lead dust and increase airborne lead levels and exposures.

Do not sweep brass !

As you may know, there are two methods that should be considered for the routine cleaning of your range. One is wet mopping and the other is using a HEPA vacuum system. Both systems prevent settled lead from becoming stirred up and exposing employees to elevated airborne lead levels.

However, you should be aware that if you use a wet-mop procedure for range cleaning, the water may need to be managed as a hazardous waste.


If you plan to use a HEPA vacuum system, make sure it is designed to be used to collect combustible dust so unburned or spilled gunpowder isn't accidentally ignited.



Safely recover 99.995% at 0.3 micron in size of Hazardous Lead Dust exhausting clean air back into the gun range

Floors and horizontal surfaces should be cleaned on a regular basis. Cleaning frequency depends on how heavily the range is used. Floor and horizontal surfaces such as booth shelves or target retrieval systems may need daily cleaning if heavily used. Otherwise, cleaning should be performed once or twice a week. Cleaning can be conducted either with a vacuum equipped with a high efficiency particulate air (HEPA) filter, or wet methods. The vacuum should be dedicated for the lead dust cleanup. Individuals performing cleaning operations should be properly trained and not try to hurry the process.

Dry sweeping or the use of compressed air to "blow down" the range should be prohibited.



COMPLIES WITH NFPA 652
PARAGRAPH 8.4.2.2.1.7 (1) TO (7)



INCREASED REVENUE, DECREASED COSTS

Housekeeping reduces risks and exposures and helps processes run more smoothly. Gun ranges that prioritize safety in the workplace are able to sell and deliver more products and services of a higher quality quicker, while using fewer resources.

**Cleanliness equals efficiency.
Exposure and disorganization consume time and
company resources without adding any value.**

A customer who receives a better product or service, faster, will probably become a repeat customer. And they'll likely become a brand advocate as well, telling others about their experience. Gun Ranges that take housekeeping seriously drive customer satisfaction from moment one. Remember that cleanliness creates a positive first impression - it sets the foundation for a good customer experience.

MFS MANUAL
FILTER SHAKER

DT DETACHABLE
RECOVERY TANK


TV-201

ORDLOC-652

VOLTAGE	120 V
HERTZ	60 Hz
PHASE	Single
WATTAGE	2400 W
POWER	3.2 HP
AMPERAGE	15.8 A
AIR FLOW	270 CFM
VAC. PRESSURE	71.5 in. H ₂ O



HEPA FILTER
99.99% EFFICIENCY
AT 0.3 MICRON



2 in. DIAM. (50MM) STATIC CONDUCTIVE TOOLKIT



3M
3 MOTORS
USED INDIVIDUALLY
OR SIMULTANEOUSLY



MANOMETER

Measuring Vacuum pressure

FBI

Filter Blockage indicator

ON/OFF

Power Source

3 MOTORS

Can be used individually,
or simultaneously



**LESS
CLOGGING
AND MORE
PRODUCTIVITY
WITH A
21 ft²
CONDUCTIVE
PLEATED FILTER**



**DUST IGNITION
PROTECTED**
DIVISION 2
CLASS II
GROUPS F, G




MFS MANUAL
FILTER SHAKER

DT DETACHABLE
RECOVERY TANK

5H 5 HEPA FILTERS
CLASS H14

4D-35L EX
DRY RECOVERY

VOLTAGE	120 V
HERTZ	60 Hz
PHASE	Single
WATTAGE	2040 W
POWER	2.7 HP
AMPERAGE	15.2 A
AIR FLOW	200 CFM
VAC. PRESSURE	90 in. H ₂ O

 **HEPA FILTER**
99.99% EFFICIENCY
AT 0.3 MICRON

SMART INVESTMENT

Establishing safe and simple cleaning procedures to ensure the health & safety of your employees, is the best investment you could make. The onboard SIDEKICK is designed to improve the overall cleaning efficiency resulting in improved productivity.

THE MOST FLEXIBLE INDUSTRIAL CLEANING TOOL A GUN RANGE CAN USE

SHIFT/GO
DUAL INLETS

DFC
DETACHABLE FILTER CHAMBER
For easy filter maintenance and replacement

DSI
DUAL SUCTION INLETS /
GATE VALVES
Easily Shift & Go and switch from wide-area cleaning to spot cleaning

DT
DETACHABLE RECOVERY TANK
For easy disposal of contaminated material



SIDEKICK
HOSE & WAND

1.5 in. DIAM. (38MM)
STATIC CONDUCTIVE SUCTION HOSE
AND CONICAL NOZZLE



SAFE FROM
ELECTROSTATIC
DISCHARGES

Ideal for cleaning along vertical surfaces, removing debris from cracks and crevices, expansion joints, stray small caliber casings and those difficult to reach nooks and crannies in the bullet trap.





LEAD-FREE ENVIRONMENT

All workers involved in housekeeping and maintenance activities should be careful not to leave the workplace wearing any contaminated clothing or equipment worn during the work shift.


Tiger-Vac shooting range/shot house vacuum systems are designed to meet the NFPA 652 Vacuum Cleaning Method requirements, clause 8.4.2.2.1.7 points 1 through 7 that define the minimum requirements that a portable vacuum must meet to be used to collect combustible particulate solids in unclassified (nonhazardous) areas, or certified by a NRTL (Nationally Recognized Testing Laboratory) for use in Division 2 Hazardous Locations for the recovery of combustible dusts.

NFPA 652 Models will ensure that members and employees do not leave the facility wearing any contaminated clothing or equipment worn during gun range activity and work shift (including shoes and undergarments), ensuring also that members and employees do not enter lunch room and VIP lounges with protective clothing and equipment unless lead dust has been removed by HEPA vacuuming, or another recognized cleaning method beforehand.

SAFE PRACTICES CAN BE EASILY ACHIEVED WITH OUR PORTABLE AND WALL-MOUNTED MODELS

Workplace lead hazards could impact employees' families as well. Lead taken home on work clothes and shoes can expose children and other household members. Employers may be legally responsible if household members are adversely affected by this "take-home" lead.


Good Housekeeping is not limited to cleaning only firing lanes. Consider cleaning one's clothes/garments.



COMPLIES WITH NFPA 652 PARAGRAPH 8.4.2.2.1.7 (1) TO (7)



AREAS TESTED FOR LEAD CONTAMINATION



HEPA FILTER
99.99% EFFICIENCY
AT 0.3 MICRON



SAFE FROM
ELECTROSTATIC
DISCHARGES

2D-1 (PCS-WM)

DRY RECOVERY

VOLTAGE	120 V
HERTZ	60 Hz
PHASE	Single
WATTAGE	1207 W
POWER	1.6 HP
AMPERAGE	10.5 A
AIR FLOW	110 CFM
VAC. PRESSURE	107 in. H ₂ O



HIGH SURFACE CLEANING

Many facilities have more than adequate cleaning processes for surfaces at the general ground level. However, it's harder to see, and clean, the accumulation of dust on surfaces like the top tracks/rails in a gun range, piping and conduit, ductwork, and exposed ceiling rafters. High surface cleaning tools target these areas, ensuring they are free from accumulated dust and debris.

In addition to reducing the risk of fire and explosion by minimizing combustible dust accumulation, high surface cleaning also provides a cleaner and brighter work environment.



1.5 in. DIAM. (38MM)

GUN RANGE OVERHEAD TRACK / RAIL CLEANING STATIC DISSIPATIVE TOOLKIT

Keep in mind that lead may be present in other areas of your facility in addition to the range. Good housekeeping is one of the most important management practices you can implement to reduce exposure to lead. You need to keep all surfaces as free as practicable of accumulated lead dust and do it in a manner that will not increase the risk of lead exposure.

A clean range has the added benefit of being more attractive to members, employees and customers.



Div.2

4H 4 HEPA FILTERS
CLASS H14

IDEAL FOR CONTAINER RANGES AND MOBILE RANGES

C-10 EX

DRY RECOVERY

VOLTAGE	120 V
HERTZ	60 Hz
PHASE	Single
WATTAGE	1207 W
POWER	1.6 HP
AMPERAGE	10.5 A
AIR FLOW	110 CFM
VAC. PRESSURE	107 in. H ₂ O



STATIC CONDUCTIVE TOOLKIT

SALES@TIGER-VAC.COM | 1 800 668-4437



TIGER-VAC.COM

Tiger-Vac inc.
11 SW 12th Ave.#112
Dania FL 33004 USA

T. (954) 925-3625
F. (954) 925-3626
E. sales@tiger-vac.com

Tiger-Vac International Inc.
2020 Dagenais Blvd. West
Laval QC H7L 5W2 Canada

T. (450) 625-0099
F. (450) 625-3388
E. sales@tiger-vac.com

Tiger-Vac Europa S.r.l.
Via Marie Curie, 17
Ozzano Emilia, Italy

T. (39) 051 79.53.52
F. (39) 051 4695077
E. info@tiger-vac.it

